



2300 South Ashland Avenue, Green Bay, WI 54307 USA  
 (920) 494-5604  
 sales@pcmc.com  
 www.pcmc.com

## ELS Servo Specifications

	<u>10"</u>	<u>13"</u>	<u>16"</u>
Web Width Clearance	10 1/4"	13 1/4"	16 3/4"
Maximum Printing Width	10"	13"	16 1/2"
Printing Stations	Up to 12 colors	Up to 12 colors	Up to 12 colors
Print Repeat	6" to 24" standard	8" to 24" standard (6" to 8" with adaptor)	8" to 24" standard (6" to 8" with adaptor)
Print Cylinder Shaft Diameter	5/8"	3/4"	3/4"
Impression Cylinder Diameter	2.86"	2.86"	2.86"
Plate Cylinder Gearing	1/8" CP	1/8" CP	1/8" CP
Print Station Frame Thickness	5/8"	5/8"	5/8"
Motorization	SERVO	SERVO	SERVO
Register	360°	360°	360°
Die Cutting Stations	2 std	2 std	2 std
Die Cutting Width	10"	13"	16"
Maximum Die Cutting Repeat	24"	24"	24"
Anvil Cylinder Diameter	3.82"	3.82"	3.82"
Removable Anvils for Die Station	2	2	2
Die Station Frame Thickness	3/4"	3/4"	3/4"
Unwind Capacity	42"	42"	42"
Rewind Capacity	42"	42"	42"
Waste Rewind Capacity	24"(42" optional)	24"(42" optional)	24"(42" optional)
Waste Rewind on Rail System	42"	42"	42"
Unwind Roll Lift	Pneumatic	Hydraulic	Hydraulic
Power Requirement	240 VAC	240 VAC	240 VAC or 480 VAC
Air Pressure	100 PSI – 7 bars	100 PSI – 7 bars	100 PSI – 7 bars
Speed	750 fpm	750 fpm	750 fpm